

## Description

The 5PB11xx is a high-performance LVCMOS clock buffer family of devices. It has an additive phase jitter of 50fs RMS.

There are five different fan-out variations available: 1:2 to 1:10.

The 5PB11xx supports a synchronous glitch-free output enable (OE) function to eliminate any potential intermediate incorrect output clock cycles when enabling or disabling outputs. It can operate from a 1.8V to 3.3V supply.

The 5PB1104 is also available in an Automotive Grade 1, AEC-Q100 qualified version.


## Typical Applications

- Industrial applications
- Automotive applications

## Features

- High-performance 1:2, 1:4, 1:6, 1:8, 1:10 LVCMOS clock buffer
- Very low pin-to-pin skew: < 50ps
- Very low additive jitter: < 50fs
- Supply voltage: 1.8V to 3.3V
- 3.3V tolerant input clock
- $f_{MAX} = 200\text{MHz}$
- Integrated serial termination for 50Ω channel
- Packaged in 8-, 14-, 16-, 20-pin TSSOP and as small as 2 × 2 mm DFN and VFQFPN packages
- Industrial (-40°C to +85°C) and extended (-40°C to +105°C) temperature ranges
- 5PB1104 available in AEC-Q100 qualified, Automotive Grade 1 (-40°C to +125°C)

## Block Diagram



# Contents

|                                                  |    |
|--------------------------------------------------|----|
| Description . . . . .                            | 1  |
| Typical Applications . . . . .                   | 1  |
| Features . . . . .                               | 1  |
| Block Diagram . . . . .                          | 1  |
| Pin Assignments – TSSOP Packages . . . . .       | 3  |
| Pin Descriptions – TSSOP Packages . . . . .      | 3  |
| Pin Assignments – DFN/VFQFPN Packages . . . . .  | 4  |
| Pin Descriptions – DFN/VFQFPN Packages . . . . . | 4  |
| Output Logic Table . . . . .                     | 5  |
| Absolute Maximum Ratings . . . . .               | 5  |
| Recommended Operating Conditions . . . . .       | 5  |
| Thermal Characteristics . . . . .                | 6  |
| DC Electrical Characteristics . . . . .          | 7  |
| AC Electrical Characteristics . . . . .          | 10 |
| Phase Noise Plots . . . . .                      | 13 |
| Test Load and Circuit . . . . .                  | 14 |
| Package Outline Drawings . . . . .               | 14 |
| Marking Diagrams (Industrial) . . . . .          | 15 |
| Marking Diagrams (Extended) . . . . .            | 16 |
| Marking Diagrams (Automotive) . . . . .          | 16 |
| Ordering Information (Industrial) . . . . .      | 17 |
| Ordering Information (Extended) . . . . .        | 18 |
| Ordering Information (Automotive) . . . . .      | 18 |
| Revision History . . . . .                       | 19 |

## Pin Assignments – TSSOP Packages

**Figure 1. Pin Assignments for TSSOP Packages**

|       |   |   |     |       |   |    |     |       |    |    |     |
|-------|---|---|-----|-------|---|----|-----|-------|----|----|-----|
| CLKIN | 1 | 8 | Y1  | CLKIN | 1 | 14 | Y1  | CLKIN | 1  | 20 | Y1  |
| 1G    | 2 | 7 | NC  | 1G    | 2 | 13 | Y3  | 1G    | 2  | 19 | Y3  |
| Y0    | 3 | 6 | VDD | Y0    | 3 | 12 | VDD | Y0    | 3  | 18 | VDD |
| GND   | 4 | 5 | NC  | GND   | 4 | 11 | Y2  | GND   | 4  | 17 | Y2  |
|       |   |   |     | VDD   | 5 | 10 | GND | VDD   | 5  | 16 | GND |
|       |   |   |     | Y4    | 6 | 9  | Y5  | Y4    | 6  | 15 | Y5  |
|       |   |   |     | GND   | 7 | 8  | VDD | GND   | 7  | 14 | VDD |
| CLKIN | 1 | 8 | Y1  | CLKIN | 1 | 16 | Y1  | Y6    | 8  | 13 | Y7  |
| 1G    | 2 | 7 | Y3  | 1G    | 2 | 15 | Y3  | VDD   | 9  | 12 | Y8  |
| Y0    | 3 | 6 | VDD | Y0    | 3 | 14 | VDD | Y9    | 10 | 11 | GND |
| GND   | 4 | 5 | Y2  | GND   | 4 | 13 | Y2  |       |    |    |     |
|       |   |   |     | VDD   | 5 | 12 | GND |       |    |    |     |
|       |   |   |     | Y4    | 6 | 11 | Y5  |       |    |    |     |
|       |   |   |     | GND   | 7 | 10 | VDD |       |    |    |     |
|       |   |   |     | Y6    | 8 | 9  | Y7  |       |    |    |     |

## Pin Descriptions – TSSOP Packages

**Table 1. Pin Descriptions for TSSOP Packages**

| Device Number | LVC MOS Clock Input | Clock Output Enable | LVC MOS Clock Output                | Supply Voltage  | Ground       |
|---------------|---------------------|---------------------|-------------------------------------|-----------------|--------------|
|               | CLKIN               | 1G                  | Y0, Y1, ... Y9                      | V <sub>DD</sub> | GND          |
| 5PB1102PGG    | 1                   | 2                   | 3, 8                                | 6               | 4            |
| 5PB1104PGG    | 1                   | 2                   | 3, 8, 5, 7                          | 6               | 4            |
| 5PB1106PGG    | 1                   | 2                   | 3, 14, 11, 13, 6, 9                 | 5, 8, 12        | 4, 7, 10     |
| 5PB1108PGG    | 1                   | 2                   | 3, 16, 13, 15, 6, 11, 8, 9          | 5, 10, 14       | 4, 7, 12     |
| 5PB1110PGG    | 1                   | 2                   | 3, 20, 17, 19, 6, 15, 8, 13, 12, 10 | 6               | 4, 7, 11, 16 |



## Output Logic Table

| Inputs |    | Output |
|--------|----|--------|
| CLKIN  | 1G | Yn     |
| X      | L  | L      |
| L      | H  | L      |
| H      | H  | H      |

After at least three cycles of input clock toggling. Output Enable function is asynchronous to eliminate any intermediate incorrect output clock cycles during transition which may cause frequency peaking to the downstream device.

## Absolute Maximum Ratings

The absolute maximum ratings are stress ratings only. Stresses greater than those listed below can cause permanent damage to the device. Functional operation of the 5PB11xx at absolute maximum ratings is not implied. Exposure to absolute maximum rating conditions may affect device reliability.

**Table 3. Absolute Maximum Ratings**

| Item                                               | Rating                     |
|----------------------------------------------------|----------------------------|
| Supply Voltage, $V_{DD}$                           | 3.8V                       |
| Output Enable and All Outputs                      | -0.4 V to $V_{DD} + 0.5$ V |
| Input Voltage, CLKIN                               | -0.4 V to 3.465V           |
| Ambient Operating Temperature (Industrial)         | -40 to +85°C               |
| Ambient Operating Temperature (Extended)           | -40 to +105°C              |
| Ambient Operating Temperature (Automotive Grade 1) | -40 to +125°C              |
| Storage Temperature                                | -65 to +150°C              |
| Junction Temperature                               | 125°C                      |
| Soldering Temperature                              | 260°C                      |

## Recommended Operating Conditions

**Table 4. Recommended Operating Conditions**

| Parameter                                          | Minimum | Typical | Maximum | Units |
|----------------------------------------------------|---------|---------|---------|-------|
| Ambient Operating Temperature (Industrial)         | -40     |         | +85     |       |
| Ambient Operating Temperature (Extended)           | -40     |         | +105    |       |
| Ambient Operating Temperature (Automotive Grade 1) | -40     |         | +125    | °C    |
| Power Supply Voltage (measured in respect to GND)  | +1.71   |         | +3.465  | V     |

# Thermal Characteristics

**Table 5. Thermal Characteristics**

| Package   | Applies to                           | $\theta_{JA}$ | $\theta_{JC}$ | $\theta_{JB}$ | Units           |
|-----------|--------------------------------------|---------------|---------------|---------------|-----------------|
| 8-TSSOP   | 5PB1102PGG, 5PB1104PGG               | 122.0         | 58.2          | 139.3         | °C/W; still air |
| 14-TSSOP  | 5PB1106PGG                           | 84.5          | 44.2          | 64.5          | °C/W; still air |
| 16-TSSOP  | 5PB1108PGG                           | 80.9          | 43.3          | 60.1          | °C/W; still air |
| 20-TSSOP  | 5PB1110PGG                           | 72.5          | 37.9          | 49.8          | °C/W; still air |
| 8-DFN     | 5PB1102CMG, 5PB1104CMG<br>5PB1104CMT | 120.2         | 99.4          | 63.3          | °C/W; still air |
| 16-VFQFPN | 5PB1106CMG, 5PB1108CMG               | 115.6         | 83.1          | 61.8          | °C/W; still air |
| 20-VFQFPN | 5PB1110NDG                           | 49.6          | 94.7          | 5.1           | °C/W; still air |

## DC Electrical Characteristics

$V_{DD} = 1.8V, 2.5V, \text{ or } 3.3V$  (see tables below)

**Table 6. DC Electrical Characteristics –  $V_{DD} = 1.8V \pm 5\%$**

| Symbol   | Parameter                                | Applies to                             | Conditions              | Minimum             | Typical | Maximum             | Units    |
|----------|------------------------------------------|----------------------------------------|-------------------------|---------------------|---------|---------------------|----------|
| $V_{DD}$ | Operating Voltage                        | All devices                            |                         | 1.71                | 1.8     | 1.89                | V        |
| $V_{IH}$ | Input High Voltage, CLKIN <sup>[1]</sup> | All devices                            |                         | $0.7 \times V_{DD}$ |         |                     | V        |
| $V_{IL}$ | Input Low Voltage, CLKIN <sup>[1]</sup>  | All devices                            |                         |                     |         | $0.3 \times V_{DD}$ | V        |
| $V_{IH}$ | Input High Voltage, 1G                   | All devices                            |                         | 1.6                 |         | $V_{DD}$            | V        |
| $V_{IL}$ | Input Low Voltage, 1G                    | All devices                            |                         |                     |         | 0.6                 | V        |
| $V_{OH}$ | Output High Voltage                      | Industrial and Extended <sup>[2]</sup> | $I_{OH} = -5mA.$        | 1.4                 |         |                     | V        |
|          | Output High Voltage                      | Automotive <sup>[3]</sup>              | $I_{OH} = -5mA.$        | 1.2                 |         |                     | V        |
| $V_{OL}$ | Output Low Voltage                       | Industrial and Extended <sup>[2]</sup> | $I_{OL} = 5mA.$         |                     |         | 0.4                 | V        |
|          | Output Low Voltage                       | Automotive <sup>[3]</sup>              | $I_{OL} = 5mA.$         |                     |         | 0.45                | V        |
| $Z_O$    | Nominal Output Impedance                 | All devices                            |                         |                     | 50      |                     | $\Omega$ |
| $C_{IN}$ | Input Capacitance                        | All devices                            | CLKIN, 1G pin.          |                     | 5       |                     | pF       |
| $I_{DD}$ | Operating Supply Current, 5PB1102        | Industrial and Extended <sup>[2]</sup> | 100MHz, no load, 25°C.  |                     | 6       | 8                   | mA       |
|          | Operating Supply Current, 5PB1104        |                                        |                         |                     | 12      | 13                  |          |
|          | Operating Supply Current, 5PB1106        |                                        |                         |                     | 15      | 18                  |          |
|          | Operating Supply Current, 5PB1108        |                                        |                         |                     | 20      | 23                  |          |
|          | Operating Supply Current, 5PB1110        |                                        |                         |                     | 23      | 27                  |          |
| $I_{DD}$ | Operating Supply Current                 | Automotive <sup>[3]</sup>              | 0.001MHz, $C_L = 5pF.$  |                     | 0.7     | 1                   | mA       |
|          |                                          |                                        | 0.008MHz, $C_L = 5pF.$  |                     | 0.7     | 1                   |          |
|          |                                          |                                        | 40MHz, $C_L = 5pF.$     |                     | 11      | 13                  |          |
|          |                                          |                                        | 100MHz, $C_L = 5pF.$    |                     | 25      | 30                  |          |
|          |                                          |                                        | 156.25MHz, $C_L = 5pF.$ |                     | 37      | 47                  |          |
|          |                                          |                                        | 200MHz, $C_L = 5pF.$    |                     | 39      | 57                  |          |
| $I_{IH}$ | Input High Leakage                       | All devices                            | $V_{IN} = V_{DD}$       |                     |         | 5                   | $\mu A$  |
| $I_{IL}$ | Input Low Leakage                        | All devices                            | $V_{IN} = 0V$           |                     |         | 5                   | $\mu A$  |

<sup>[1]</sup> Nominal switching threshold is  $V_{DD}/2$ .

<sup>[2]</sup> 5PB11xxPGGI, 5PB11xxPGGK, 5PB11xxCMGI, 5PB11xxCMGK.  $T_A = -40^\circ C$  to  $+105^\circ C$  unless stated otherwise.

<sup>[3]</sup> 5PB1104CMG1 and 5PB1104CMT1 only.  $T_A = -40^\circ C$  to  $+125^\circ C$  unless stated otherwise.

**Table 7. DC Electrical Characteristics –  $V_{DD} = 2.5V \pm 5\%$**

| Symbol   | Parameter                                | Applies to                             | Conditions               | Minimum             | Typical | Maximum             | Units    |
|----------|------------------------------------------|----------------------------------------|--------------------------|---------------------|---------|---------------------|----------|
| $V_{DD}$ | Operating Voltage                        | All devices                            |                          | 2.375               | 2.5     | 2.625               | V        |
| $V_{IH}$ | Input High Voltage, CLKIN <sup>[1]</sup> | All devices                            |                          | $0.7 \times V_{DD}$ |         |                     | V        |
| $V_{IL}$ | Input Low Voltage, CLKIN <sup>[1]</sup>  | All devices                            |                          |                     |         | $0.3 \times V_{DD}$ | V        |
| $V_{IH}$ | Input High Voltage, 1G                   | All devices                            |                          | 1.8                 |         | $V_{DD}$            | V        |
| $V_{IL}$ | Input Low Voltage, 1G                    | All devices                            |                          |                     |         | 0.7                 | V        |
| $V_{OH}$ | Output High Voltage                      | Industrial and Extended <sup>[2]</sup> | $I_{OH} = -8mA$ .        | 1.9                 |         |                     | V        |
|          | Output High Voltage                      | Automotive <sup>[3]</sup>              | $I_{OH} = -8mA$ .        | 1.6                 |         |                     | V        |
| $V_{OL}$ | Output Low Voltage                       | Industrial and Extended <sup>[2]</sup> | $I_{OL} = 8mA$ .         |                     |         | 0.5                 | V        |
|          | Output Low Voltage                       | Automotive <sup>[3]</sup>              | $I_{OL} = 8mA$ .         |                     |         | 0.625               | V        |
| $Z_O$    | Nominal Output Impedance                 | All devices                            |                          |                     | 50      |                     | $\Omega$ |
| $C_{IN}$ | Input Capacitance                        | All devices                            | CLKIN, 1G pin.           |                     | 5       |                     | pF       |
| $I_{DD}$ | Operating Supply Current, 5PB1102        | Industrial and Extended <sup>[2]</sup> | 100MHz, no load, 25°C.   |                     | 9       | 11                  | mA       |
|          | Operating Supply Current, 5PB1104        |                                        |                          |                     | 15      | 18                  |          |
|          | Operating Supply Current, 5PB1106        |                                        |                          |                     | 21      | 24                  |          |
|          | Operating Supply Current, 5PB1108        |                                        |                          |                     | 27      | 31                  |          |
|          | Operating Supply Current, 5PB1110        |                                        |                          |                     | 32      | 37                  |          |
| $I_{DD}$ | Operating Supply Current                 | Automotive <sup>[3]</sup>              | 0.001MHz, $C_L = 5pF$ .  |                     | 0.9     | 1.3                 | mA       |
|          |                                          |                                        | 0.008MHz, $C_L = 5pF$ .  |                     | 0.9     | 1.3                 |          |
|          |                                          |                                        | 40MHz, $C_L = 5pF$ .     |                     | 15      | 17                  |          |
|          |                                          |                                        | 100MHz, $C_L = 5pF$ .    |                     | 35      | 42                  |          |
|          |                                          |                                        | 156.25MHz, $C_L = 5pF$ . |                     | 52      | 67                  |          |
|          |                                          |                                        | 200MHz, $C_L = 5pF$ .    |                     | 56      | 80                  |          |
| $I_{IH}$ | Input High Leakage                       | All devices                            | $V_{IN} = V_{DD}$        |                     |         | 5                   | $\mu A$  |
| $I_{IL}$ | Input Low Leakage                        | All devices                            | $V_{IN} = 0V$            |                     |         | 5                   | $\mu A$  |

<sup>[1]</sup> Nominal switching threshold is  $V_{DD}/2$ .

<sup>[2]</sup> 5PB11xxPGGI, 5PB11xxPGGK, 5PB11xxCMGI, 5PB11xxCMGK.  $T_A = -40^\circ C$  to  $+105^\circ C$  unless stated otherwise.

<sup>[3]</sup> 5PB1104CMG1 and 5PB1104CMT1 only.  $T_A = -40^\circ C$  to  $+125^\circ C$  unless stated otherwise.

**Table 8. DC Electrical Characteristics –  $V_{DD} = 3.3V \pm 5\%$**

| Symbol   | Parameter                                | Applies to                             | Conditions               | Minimum             | Typical | Maximum             | Units    |
|----------|------------------------------------------|----------------------------------------|--------------------------|---------------------|---------|---------------------|----------|
| $V_{DD}$ | Operating Voltage                        | All devices                            |                          | 3.135               | 3.3     | 3.465               | V        |
| $V_{IH}$ | Input High Voltage, CLKIN <sup>[1]</sup> | All devices                            |                          | $0.7 \times V_{DD}$ |         |                     | V        |
| $V_{IL}$ | Input Low Voltage, CLKIN <sup>[1]</sup>  | All devices                            |                          |                     |         | $0.3 \times V_{DD}$ | V        |
| $V_{IH}$ | Input High Voltage, 1G                   | Industrial and Extended <sup>[2]</sup> |                          | 2.0                 |         | $V_{DD}$            | V        |
| $V_{IH}$ | Input High Voltage, 1G                   | Automotive <sup>[3]</sup>              |                          | 2.1                 |         | $V_{DD}$            | V        |
| $V_{IL}$ | Input Low Voltage, 1G                    | All devices                            |                          |                     |         | 0.8                 | V        |
| $V_{OH}$ | Output High Voltage                      | Industrial and Extended <sup>[2]</sup> | $I_{OH} = -12mA$ .       | 2.4                 |         |                     | V        |
|          | Output High Voltage                      | Automotive <sup>[3]</sup>              | $I_{OH} = -12mA$ .       | 2.1                 |         |                     | V        |
| $V_{OL}$ | Output Low Voltage                       | Industrial and Extended <sup>[2]</sup> | $I_{OL} = 12mA$ .        |                     |         | 0.7                 | V        |
|          | Output Low Voltage                       | Automotive <sup>[3]</sup>              | $I_{OL} = 12mA$ .        |                     |         | 0.825               | V        |
| $Z_O$    | Nominal Output Impedance                 | All devices                            |                          |                     | 50      |                     | $\Omega$ |
| $C_{IN}$ | Input Capacitance                        | All devices                            | CLKIN, 1G pin.           |                     | 5       |                     | pF       |
| $I_{DD}$ | Operating Supply Current, 5PB1102        | Industrial and Extended <sup>[2]</sup> | 100MHz, no load, 25°C.   |                     | 12      | 13                  | mA       |
|          | Operating Supply Current, 5PB1104        |                                        |                          |                     | 20      | 22                  |          |
|          | Operating Supply Current, 5PB1106        |                                        |                          |                     | 25      | 30                  |          |
|          | Operating Supply Current, 5PB1108        |                                        |                          |                     | 35      | 38                  |          |
|          | Operating Supply Current, 5PB1110        |                                        |                          |                     | 40      | 45                  |          |
| $I_{DD}$ | Operating Supply Current                 | Automotive <sup>[3]</sup>              | 0.001MHz, $C_L = 5pF$ .  |                     | 1.2     | 1.7                 | mA       |
|          |                                          |                                        | 0.008MHz, $C_L = 5pF$ .  |                     | 1.2     | 1.7                 |          |
|          |                                          |                                        | 40MHz, $C_L = 5pF$ .     |                     | 19      | 22                  |          |
|          |                                          |                                        | 100MHz, $C_L = 5pF$ .    |                     | 45      | 54                  |          |
|          |                                          |                                        | 156.25MHz, $C_L = 5pF$ . |                     | 67      | 87                  |          |
|          |                                          |                                        | 200MHz, $C_L = 5pF$ .    |                     | 75      | 107                 |          |
| $I_{IH}$ | Input High Leakage                       | All devices                            | $V_{IN} = V_{DD}$        |                     |         | 5                   | $\mu A$  |
| $I_{IL}$ | Input Low Leakage                        | All devices                            | $V_{IN} = 0V$            |                     |         | 5                   | $\mu A$  |

<sup>[1]</sup> Nominal switching threshold is  $V_{DD}/2$ .

<sup>[2]</sup> 5PB11xxPGGI, 5PB11xxPGGK, 5PB11xxCMGI, 5PB11xxCMGK.  $T_A = -40^\circ C$  to  $+105^\circ C$  unless stated otherwise.

<sup>[3]</sup> 5PB1104CMG1 and 5PB1104CMT1 only.  $T_A = -40^\circ C$  to  $+125^\circ C$  unless stated otherwise.

## AC Electrical Characteristics

$V_{DD} = 1.8V, 2.5V, \text{ or } 3.3V$  (see tables below).

**Table 9. AC Electrical Characteristics –  $V_{DD} = 1.8V \pm 5\%$**

| Symbol         | Parameter                         | Applies to                             | Conditions                                                   | Minimum | Typical | Maximum | Units  |
|----------------|-----------------------------------|----------------------------------------|--------------------------------------------------------------|---------|---------|---------|--------|
|                | Input Frequency                   | All devices                            |                                                              | 0       |         | 200     | MHz    |
| $t_{OR}$       | Output Rise Time (2pF load)       | Industrial and Extended <sup>[1]</sup> | 0.36V to 1.44V, $C_L = 2pF$ .                                |         | 0.5     | 0.75    | ns     |
| $t_{OF}$       | Output Fall Time (2pF load)       | Industrial and Extended <sup>[1]</sup> | 1.44V to 0.36V, $C_L = 2pF$ .                                |         | 0.5     | 0.75    | ns     |
| $t_{OR}$       | Output Rise Time (5pF load)       | Industrial and Extended <sup>[1]</sup> | 0.36V to 1.44V, $C_L = 5pF$ .                                |         | 0.8     | 1.0     | ns     |
| $t_{OF}$       | Output Fall Time (5pF load)       | Industrial and Extended <sup>[1]</sup> | 1.44V to 0.36V, $C_L = 5pF$ .                                |         | 0.8     | 1.0     | ns     |
| $t_{OR}$       | Output Rise Time (5pF load)       | Automotive <sup>[2]</sup>              | 0.36V to 1.44V, $C_L = 5pF$ .                                |         | 0.65    | 1.2     | ns     |
| $t_{OF}$       | Output Fall Time (5pF load)       | Automotive <sup>[2]</sup>              | 1.44V to 0.36V, $C_L = 5pF$ .                                |         | 0.65    | 1.2     | ns     |
| $t_{START-UP}$ | Start-up Time                     | All devices                            | Part start-up time for valid outputs after $V_{DD}$ ramp-up. |         |         | 3       | ms     |
| $t_{PD}$       | Propagation Delay <sup>[3]</sup>  | Industrial and Extended <sup>[1]</sup> |                                                              | 1.5     |         | 2.5     | ns     |
|                |                                   | Automotive <sup>[2]</sup>              |                                                              | 1.0     |         | 3.4     | ns     |
|                | Buffer Additive Phase Jitter, RMS | Industrial and Extended <sup>[1]</sup> | 156.25MHz, Integration Range: 12kHz–20MHz.                   |         |         | 0.05    | ps     |
|                |                                   | Automotive <sup>[2]</sup>              | 156.25MHz, Integration Range: 12kHz–20MHz.                   |         |         | 0.06    | ps     |
|                | Output to Output Skew, 5PB1102/04 | Industrial and Extended <sup>[1]</sup> | Rising edges at $V_{DD}/2$ . <sup>[4]</sup>                  |         | 35      | 50      | ps     |
|                | Output to Output Skew, 5PB1106    | Industrial and Extended <sup>[1]</sup> | Rising edges at $V_{DD}/2$ . <sup>[4]</sup>                  |         | 35      | 58      | ps     |
|                | Output to Output Skew, 5PB1108/10 | Industrial and Extended <sup>[1]</sup> | Rising edges at $V_{DD}/2$ . <sup>[4]</sup>                  |         | 45      | 65      | ps     |
|                | Output to Output Skew             | Automotive <sup>[2]</sup>              | Rising edges at $V_{DD}/2$ . <sup>[4]</sup>                  |         | 35      | 87      | ps     |
|                | Device to Device Skew             | All devices                            | Rising edges at $V_{DD}/2$ .                                 |         |         | 200     | ps     |
| $t_{EN}$       | Output Enable Time                | All devices                            | $C_L \leq 5pF$ .                                             |         |         | 3       | cycles |
| $t_{DIS}$      | Output Disable Time               | All devices                            | $C_L \leq 5pF$ .                                             |         |         | 3       | cycles |
| $t_{DC}$       | Duty Cycle <sup>[5]</sup>         | All devices                            |                                                              |         | 50      |         | %      |

<sup>1</sup> 5PB11xxPGGI, 5PB11xxPGGK, 5PB11xxCMGI, 5PB11xxCMGK.  $T_A = -40^\circ C$  to  $+105^\circ C$  unless stated otherwise.

<sup>2</sup> 5PB1104CMG1 and 5PB1104CMT1 only.  $T_A = -40^\circ C$  to  $+125^\circ C$  unless stated otherwise.

<sup>3</sup> With rail-to-rail input clock.

<sup>4</sup> Between any 2 outputs with equal loading.

<sup>5</sup> Duty cycle on outputs will match incoming clock duty cycle when  $V_{IH}$  on CLKIN pin equals  $V_{DD}$  power supply voltage. Consult Renesas for tight duty cycle clock generators.

**Table 10. AC Electrical Characteristics –  $V_{DD} = 2.5V \pm 5\%$** 

| Symbol         | Parameter                                    | Applies to                             | Conditions                                                   | Minimum | Typical | Maximum | Units  |
|----------------|----------------------------------------------|----------------------------------------|--------------------------------------------------------------|---------|---------|---------|--------|
|                | Input Frequency                              | All devices                            |                                                              | 0       |         | 200     | MHz    |
| $t_{OR}$       | Output Rise Time (2pF load)                  | Industrial and Extended <sup>[1]</sup> | 0.5V to 2.0V, $C_L = 2pF$ .                                  |         | 0.4     | 0.7     | ns     |
| $t_{OF}$       | Output Fall Time (2pF load)                  | Industrial and Extended <sup>[1]</sup> | 2.0V to 0.5V, $C_L = 2pF$ .                                  |         | 0.4     | 0.7     | ns     |
| $t_{OR}$       | Output Rise Time (5pF load)                  | Industrial and Extended <sup>[1]</sup> | 0.5V to 2.0V, $C_L = 5pF$ .                                  |         | 0.75    | 1.0     | ns     |
| $t_{OF}$       | Output Fall Time (5pF load)                  | Industrial and Extended <sup>[1]</sup> | 2.0V to 0.5V, $C_L = 5pF$ .                                  |         | 0.75    | 1.0     | ns     |
| $t_{OR}$       | Output Rise Time (5pF load)                  | Automotive <sup>[2]</sup>              | 0.5V to 2.0V, $C_L = 5pF$ .                                  |         | 0.63    | 1.2     | ns     |
| $t_{OF}$       | Output Fall Time (5pF load)                  | Automotive <sup>[2]</sup>              | 2.0V to 0.5V, $C_L = 5pF$ .                                  |         | 0.63    | 1.2     | ns     |
| $t_{START-UP}$ | Start-up Time                                | All devices                            | Part start-up time for valid outputs after $V_{DD}$ ramp-up. |         |         | 3       | ms     |
| $t_{PD}$       | Propagation Delay, 5PB1102/04 <sup>[3]</sup> | Industrial and Extended <sup>[1]</sup> |                                                              | 1.9     |         | 2.9     | ns     |
|                | Propagation Delay, 5PB1106/08 <sup>[3]</sup> | Industrial and Extended <sup>[1]</sup> |                                                              | 2.0     |         | 3.3     | ns     |
|                | Propagation Delay, 5PB1110 <sup>[3]</sup>    | Industrial and Extended <sup>[1]</sup> |                                                              | 2.0     |         | 3.0     | ns     |
|                | Propagation Delay <sup>[3]</sup>             | Automotive <sup>[2]</sup>              |                                                              | 1.0     |         | 4.5     | ns     |
|                | Buffer Additive Phase Jitter, RMS            | Industrial and Extended <sup>[1]</sup> | 156.25MHz, Integration Range: 12kHz–20MHz.                   |         |         | 0.05    | ps     |
|                |                                              | Automotive <sup>[2]</sup>              | 156.25MHz, Integration Range: 12kHz–20MHz.                   |         |         | 0.06    | ps     |
|                | Output to Output Skew, 5PB1102/04            | Industrial and Extended <sup>[1]</sup> | Rising edges at $V_{DD}/2$ . <sup>[4]</sup>                  |         | 35      | 50      | ps     |
|                | Output to Output Skew, 5PB1106               | Industrial and Extended <sup>[1]</sup> | Rising edges at $V_{DD}/2$ . <sup>[4]</sup>                  |         | 35      | 58      | ps     |
|                | Output to Output Skew, 5PB1108/10            | Industrial and Extended <sup>[1]</sup> | Rising edges at $V_{DD}/2$ . <sup>[4]</sup>                  |         | 45      | 65      | ps     |
|                | Output to Output Skew                        | Automotive <sup>[2]</sup>              | Rising edges at $V_{DD}/2$ . <sup>[4]</sup>                  |         | 35      | 87      | ps     |
|                | Device to Device Skew                        | All devices                            | Rising edges at $V_{DD}/2$ .                                 |         |         | 200     | ps     |
| $t_{EN}$       | Output Enable Time                           | All devices                            | $C_L \leq 5pF$ .                                             |         |         | 3       | cycles |
| $t_{DIS}$      | Output Disable Time                          | All devices                            | $C_L \leq 5pF$ .                                             |         |         | 3       | cycles |
| $t_{DC}$       | Duty Cycle <sup>[5]</sup>                    | All devices                            |                                                              |         | 50      |         | %      |

<sup>1</sup> 5PB11xxPGGI, 5PB11xxPGGK, 5PB11xxCMGI, 5PB11xxCMGK.  $T_A = -40^\circ C$  to  $+105^\circ C$  unless stated otherwise.

<sup>2</sup> 5PB1104CMG1 and 5PB1104CMT1 only.  $T_A = -40^\circ C$  to  $+125^\circ C$  unless stated otherwise.

<sup>3</sup> With rail-to-rail input clock.

<sup>4</sup> Between any 2 outputs with equal loading.

<sup>5</sup> Duty cycle on outputs will match incoming clock duty cycle when  $V_{IH}$  on CLKIN pin equals  $V_{DD}$  power supply voltage. Consult Renesas for tight duty cycle clock generators.

**Table 11. AC Electrical Characteristics –  $V_{DD} = 3.3V \pm 5\%$**

| Symbol         | Parameter                                    | Applies to                             | Conditions                                                   | Minimum | Typical | Maximum | Units  |
|----------------|----------------------------------------------|----------------------------------------|--------------------------------------------------------------|---------|---------|---------|--------|
|                | Input Frequency                              | All devices                            |                                                              | 0       |         | 200     | MHz    |
| $t_{OR}$       | Output Rise Time (2pF load)                  | Industrial and Extended <sup>[1]</sup> | 0.66V to 2.64V, $C_L = 2pF$ .                                |         | 0.45    | 0.6     | ns     |
| $t_{OF}$       | Output Fall Time (2pF load)                  | Industrial and Extended <sup>[1]</sup> | 2.64V to 0.66V, $C_L = 2pF$ .                                |         | 0.45    | 0.6     | ns     |
| $t_{OR}$       | Output Rise Time (5pF load)                  | Industrial and Extended <sup>[1]</sup> | 0.66V to 2.64V, $C_L = 5pF$ .                                |         | 0.7     | 1.0     | ns     |
| $t_{OF}$       | Output Fall Time (5pF load)                  | Industrial and Extended <sup>[1]</sup> | 2.64V to 0.66V, $C_L = 5pF$ .                                |         | 0.7     | 1.0     | ns     |
| $t_{OR}$       | Output Rise Time (5pF load)                  | Automotive <sup>[2]</sup>              | 0.66V to 2.64V, $C_L = 5pF$ .                                |         | 0.61    | 1.2     | ns     |
| $t_{OF}$       | Output Fall Time (5pF load)                  | Automotive <sup>[2]</sup>              | 2.64V to 0.66V, $C_L = 5pF$ .                                |         | 0.61    | 1.2     | ns     |
| $t_{START-UP}$ | Start-up Time                                | All devices                            | Part start-up time for valid outputs after $V_{DD}$ ramp-up. |         |         | 3       | ms     |
| $t_{PD}$       | Propagation Delay, 5PB1102/04 <sup>[3]</sup> | Industrial and Extended <sup>[1]</sup> |                                                              | 1.7     |         | 2.4     | ns     |
|                | Propagation Delay, 5PB1106/08 <sup>[3]</sup> | Industrial and Extended <sup>[1]</sup> |                                                              | 1.7     |         | 2.7     | ns     |
|                | Propagation Delay, 5PB1110 <sup>[3]</sup>    | Industrial and Extended <sup>[1]</sup> |                                                              | 1.7     |         | 2.5     | ns     |
|                | Propagation Delay <sup>[3]</sup>             | Automotive <sup>[2]</sup>              |                                                              | 1.0     |         | 3.4     | ns     |
|                | Buffer Additive Phase Jitter, RMS            | All devices                            | 156.25MHz, Integration Range: 12kHz–20MHz.                   |         |         | 0.05    | ps     |
|                | Output to Output Skew, 5PB1102/04            | Industrial and Extended <sup>[1]</sup> | Rising edges at $V_{DD}/2$ . <sup>[4]</sup>                  |         | 35      | 50      | ps     |
|                | Output to Output Skew, 5PB1106               | Industrial and Extended <sup>[1]</sup> | Rising edges at $V_{DD}/2$ . <sup>[4]</sup>                  |         | 35      | 58      | ps     |
|                | Output to Output Skew, 5PB1108/10            | Industrial and Extended <sup>[1]</sup> | Rising edges at $V_{DD}/2$ . <sup>[4]</sup>                  |         | 45      | 65      | ps     |
|                | Output to Output Skew                        | Automotive <sup>[2]</sup>              | Rising edges at $V_{DD}/2$ . <sup>[4]</sup>                  |         | 35      | 87      | ps     |
|                | Device to Device Skew                        | All devices                            | Rising edges at $V_{DD}/2$ .                                 |         |         | 200     | ps     |
| $t_{EN}$       | Output Enable Time                           | All devices                            | $C_L \leq 5pF$ .                                             |         |         | 3       | cycles |
| $t_{DIS}$      | Output Disable Time                          | All devices                            | $C_L \leq 5pF$ .                                             |         |         | 3       | cycles |
| $t_{DC}$       | Duty Cycle <sup>[5]</sup>                    | All devices                            |                                                              |         | 50      |         | %      |

<sup>1</sup> 5PB11xxPGGI, 5PB11xxPGGK, 5PB11xxCMGI, 5PB11xxCMGK.  $T_A = -40^\circ C$  to  $+105^\circ C$  unless stated otherwise.

<sup>2</sup> 5PB1104CMG1 and 5PB1104CMT1 only.  $T_A = -40^\circ C$  to  $+125^\circ C$  unless stated otherwise.


<sup>3</sup> With rail-to-rail input clock.

<sup>4</sup> Between any 2 outputs with equal loading.


<sup>5</sup> Duty cycle on outputs will match incoming clock duty cycle when  $V_{IH}$  on CLKIN pin equals  $V_{DD}$  power supply voltage. Consult Renesas for tight duty cycle clock generators.

## Phase Noise Plots

The phase noise plots show the low additive jitter of the 5PB11xx high-performance buffer. With an integration range of 12kHz to 20MHz, the reference input has about 58.9fs of RMS phase jitter while the output of 5PB11xx has about 70.9fs of RMS phase jitter. This results in a low additive phase jitter of only 39fs.




Reference Phase Noise 58.9fs (12kHz to 20MHz)



Output Phase Noise 70.9fs (12kHz to 20MHz)

## Test Load and Circuit



## Package Outline Drawings

The package outline drawings are appended at the end of this document and are accessible from the link below. The package information is the most current data available.

[www.idt.com/document/psc/8-tssop-package-outline-drawing-44-mm-body-065mm-pitch-pgg8d1](http://www.idt.com/document/psc/8-tssop-package-outline-drawing-44-mm-body-065mm-pitch-pgg8d1)

[www.idt.com/document/psc/14-tssop-package-outline-drawing-44mm-body-065mm-pitch-pgg14t1](http://www.idt.com/document/psc/14-tssop-package-outline-drawing-44mm-body-065mm-pitch-pgg14t1)

[www.idt.com/document/psc/16-tssop-package-outline-drawing-44mm-body-065mm-pitch-pgg16t1](http://www.idt.com/document/psc/16-tssop-package-outline-drawing-44mm-body-065mm-pitch-pgg16t1)

[www.idt.com/document/psc/20-tssop-package-outline-drawing-44-mm-body-065mm-pitch-pgg20d1](http://www.idt.com/document/psc/20-tssop-package-outline-drawing-44-mm-body-065mm-pitch-pgg20d1)


[www.idt.com/document/psc/cm8-package-outline-drawing-20-x-20-x-05-mm-body-05mm-pitch-dfn](http://www.idt.com/document/psc/cm8-package-outline-drawing-20-x-20-x-05-mm-body-05mm-pitch-dfn)

[www.idt.com/document/psc/cm16-package-outline-drawing-25-x-25-x-05-mm-body-040mm-pitch-vfqfn](http://www.idt.com/document/psc/cm16-package-outline-drawing-25-x-25-x-05-mm-body-040mm-pitch-vfqfn)


[www.idt.com/document/psc/20-vfqfn-package-outline-drawing-30-x-30-x-090-mm-040mm-pitch-165-x-165-mm-epad-ndg20p2](http://www.idt.com/document/psc/20-vfqfn-package-outline-drawing-30-x-30-x-090-mm-040mm-pitch-165-x-165-mm-epad-ndg20p2)

[www.idt.com/document/psc/dfn-8-package-outline-drawing-20-x-20-x-075-mm-body-050mm-pitch-cmt8d1](http://www.idt.com/document/psc/dfn-8-package-outline-drawing-20-x-20-x-075-mm-body-050mm-pitch-cmt8d1)


## Marking Diagrams (Industrial)




8-pin TSSOP




14-pin TSSOP




16-pin TSSOP




20-pin TSSOP




8-pin DFN



16-pin VFQFPN




16-pin VFQFPN




20-pin VFQFPN

- “AA” denotes the last two digits of the part number for 8-TSSOP and DFN (e.g. 02, 04).
- “\*\*\*” is the lot sequence.
- “XXX” denotes the last three characters of the Asm lot (20-VFQFPN only).
- “YYWW”, “YWW”, “YW”, or “Y” is the last digit(s) of the year and work week that the part was assembled.
- “\$” denotes the mark code.
- “G” after the two-letter package code denotes RoHS compliant package.
- “I” denotes industrial temperature range device.


## Marking Diagrams (Extended)




8-pin TSSOP



14-pin TSSOP




16-pin TSSOP




20-pin TSSOP




8-pin DFN



16-pin VFQFPN




16-pin VFQFPN




20-pin VFQFPN

- “AA” denotes the last two digits of the part number for 8-TSSOP and DFN (e.g. 02, 04).
- “\*\*” is the lot sequence.
- “XXX” denotes the last three characters of the Asm lot (20-VFQFPN only).
- “YYWW”, “YWW”, “YW”, or “Y” is the last digit(s) of the year and week that the part was assembled.
- “\$” denotes the mark code.
- “G” after the two-letter package code denotes RoHS compliant package.
- “K” denotes extended temperature range device.

## Marking Diagrams (Automotive)



8-pin DFN



8-pin DFN (wetable flank)

- Line 1: truncated part number; last number is the temperature grade: 1 = Automotive Grade 1.
- “YW” is the last digit of the year and work week that the part was assembled.
- “\*\*” denotes the lot sequence number.

## Ordering Information (Industrial)

| Orderable Part Number | Package                        | Carrier Type  | Temperature  |
|-----------------------|--------------------------------|---------------|--------------|
| 5PB1102PGGI           | 4.4mm body, 8-TSSOP            | Tubes         | -40 to +85°C |
| 5PB1102PGGI8          |                                | Tape and Reel |              |
| 5PB1104PGGI           |                                | Tubes         |              |
| 5PB1104PGGI8          |                                | Tape and Reel |              |
| 5PB1106PGGI           | 4.4mm body, 14-TSSOP           | Tubes         |              |
| 5PB1106PGGI8          |                                | Tape and Reel |              |
| 5PB1108PGGI           | 4.4mm body, 16-TSSOP           | Tubes         |              |
| 5PB1108PGGI8          |                                | Tape and Reel |              |
| 5PB1110PGGI           | 4.4mm body, 20-TSSOP           | Tubes         |              |
| 5PB1110PGGI8          |                                | Tape and Reel |              |
| 5PB1102CMGI           | 2.0 × 2.0 × 0.5 mm, 8-DFN      | Cut Tape      |              |
| 5PB1102CMGI8          |                                | Tape and Reel |              |
| 5PB1104CMGI           |                                | Cut Tape      |              |
| 5PB1104CMGI8          |                                | Tape and Reel |              |
| 5PB1104CMGI/W*        |                                | Tape and Reel |              |
| 5PB1106CMGI           | 2.5 × 2.5 × 0.5 mm, 16-VFQFPN  | Cut Tape      |              |
| 5PB1106CMGI8          |                                | Tape and Reel |              |
| 5PB1108CMGI           |                                | Cut Tape      |              |
| 5PB1108CMGI8          |                                | Tape and Reel |              |
| 5PB1110NDGI           | 3.0 × 3.0 × 0.90 mm, 20-VFQFPN | Tubes         |              |
| 5PB1110NDGI8          |                                | Tape and Reel |              |

\* "/W" stands for tape and reel with pin 1 orientation: EIA-481-D. All other tape and reels options come with EIA-481-C pin 1 orientation.

## Ordering Information (Extended)

| Orderable Part Number | Package                        | Carrier Type  | Temperature   |
|-----------------------|--------------------------------|---------------|---------------|
| 5PB1102PGGK           | 4.4mm body, 8-TSSOP            | Tubes         | -40 to +105°C |
| 5PB1102PGGK8          |                                | Tape and Reel |               |
| 5PB1104PGGK           |                                | Tubes         |               |
| 5PB1104PGGK8          |                                | Tape and Reel |               |
| 5PB1106PGGK           | 4.4mm body, 14-TSSOP           | Tubes         |               |
| 5PB1106PGGK8          |                                | Tape and Reel |               |
| 5PB1108PGGK           | 4.4mm body, 16-TSSOP           | Tubes         |               |
| 5PB1108PGGK8          |                                | Tape and Reel |               |
| 5PB1110PGGK           | 4.4mm body, 20-TSSOP           | Tubes         |               |
| 5PB1110PGGK8          |                                | Tape and Reel |               |
| 5PB1102CMGK           | 2.0 × 2.0 × 0.5 mm, 8-DFN      | Cut Tape      |               |
| 5PB1102CMGK8          |                                | Tape and Reel |               |
| 5PB1104CMGK           |                                | Cut Tape      |               |
| 5PB1104CMGK8          |                                | Tape and Reel |               |
| 5PB1106CMGK           | 2.5 × 2.5 × 0.5 mm, 16-VFQFPN  | Cut Tape      |               |
| 5PB1106CMGK8          |                                | Tape and Reel |               |
| 5PB1108CMGK           |                                | Cut Tape      |               |
| 5PB1108CMGK8          |                                | Tape and Reel |               |
| 5PB1110NDGK           | 3.0 × 3.0 × 0.90 mm, 20-VFQFPN | Tubes         |               |
| 5PB1110NDGK8          |                                | Tape and Reel |               |






“G” after the two-letter package code denotes Pb-Free configuration, RoHS compliant.

## Ordering Information (Automotive)

| Orderable Part Number | Package                                      | Carrier Type  | Temperature    |
|-----------------------|----------------------------------------------|---------------|----------------|
| 5PB1104CMG1           | 2.0 × 2.0 × 0.5 mm, 8-DFN                    | Cut Tape      | -40° to +125°C |
| 5PB1104CMG18          |                                              | Tape and Reel |                |
| 5PB1104CMT1           | 2.0 × 2.0 × 0.5 mm, 8-DFN,<br>Wettable flank | Cut Tape      | -40° to +125°C |
| 5PB1104CMT18          |                                              | Tape and Reel |                |


## Revision History

| Revision Date      | Description of Change                                                                                                                                                 |
|--------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| September 29, 2020 | Updated marking diagrams for 5PB1106/08/10PGGI and 5PB1106/08/10PGGK.                                                                                                 |
| January 31, 2020   | Rebranded the document as Renesas. No technical changes were made.                                                                                                    |
| December 4, 2019   | Added Input High and Low Leakage parameters to <a href="#">Table 6</a> , <a href="#">Table 7</a> , and <a href="#">Table 8</a>                                        |
| May 31, 2019       | <ul style="list-style-type: none"> <li>▪ Added 5PB1104CMT1 wettable flank package information.</li> <li>▪ Updated Propagation Delay values for automotive.</li> </ul> |
| December 18, 2018  | <ul style="list-style-type: none"> <li>▪ Updated <math>t_{PD}</math> and skew values.</li> <li>▪ Added 5PB1104CMG1 automotive part information.</li> </ul>            |
| October 24, 2018   | Initial release.                                                                                                                                                      |



NOTES:



1. ALL DIMENSIONING AND TOLERANCING CONFORM TO ANSI Y14.5M-1982
2. ALL DIMENSION ARE IN MM.



RECOMMENDED LAND PATTERN DIMENSIONS


- NOTES:
- 1. ALL DIMENSIONS ARE IN MILLIMETERS

| Package Revision History |         |                 |
|--------------------------|---------|-----------------|
| Date Created             | Rev No. | Description     |
|                          |         |                 |
| July 27, 2018            | Rev 00  | Initial Release |



NOTE:



1. ALL DIMENSIONS ARE IN MILLIMETERS



LAND PATTERN DIMENSIONS


NOTE:  
1. ALL DIMENSIONS ARE IN MILLIMETERS

| Package Revision History |         |                    |
|--------------------------|---------|--------------------|
| Date Created             | Rev No. | Description        |
| Mar, 10 2017             | Rev 01  | Added Land Pattern |
| Dec, 19 2017             | Rev 02  | New Format         |



NOTE:






1. ALL DIMENSIONS ARE IN MILLIMETERS



LAND PATTERN DIMENSIONS

NOTE:  
1. ALL DIMENSIONS ARE IN MILLIMETERS

| Package Revision History |         |                                |
|--------------------------|---------|--------------------------------|
| Date Created             | Rev No. | Description                    |
| Jan 26, 2018             | Rev 00  | Revised from PSC-4056-02 PGG16 |



SECTION A-A


NOTES:

1. ALL DIMENSIONING AND TOLERANCING CONFORM TO ANSI Y14.5M-1982  
2. ALL DIMENSION ARE IN MM.


### RECOMMENDED LAND PATTERN DIMENSIONS

1. ALL DIMENSIONS ARE IN MILLIMETERS


| REVISIONS                                    |     |                     |        |
|----------------------------------------------|-----|---------------------|--------|
| DATE CREATED                                 | REV | DESCRIPTION         | AUTHOR |
| 09/18/14                                     | 00  | INITIAL RELEASE     | J.HUA  |
| 4/5/18                                       | 01  | CHANGE VFQFN to DFN | R.C    |
| NOTE: REFER TO DCP FOR OFFICIAL RELEASE DATE |     |                     |        |



TOP VIEW



SIDE VIEW




BOTTOM VIEW

NOTES:

1. ALL DIMENSIONING AND TOLERANCING CONFORM TO ANSI Y14.5M-1982
2. ALL DIMENSIONS ARE IN MILLIMETERS

|                                |         |                                                                                                                                                                                                      |               |
|--------------------------------|---------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|
| TOLERANCES<br>UNLESS SPECIFIED |         |  <b>IDT</b> 6024 SILVER CREEK VALLEY ROAD<br>San Jose, CA 95138<br>PHONE: (408) 284-8200<br>FAX: (408) 492-8674 |               |
| DECIMAL                        | ANGULAR |                                                                                                                                                                                                      |               |
| XX±                            | ±       | <b>TITLE</b> CMC8 Package Outline Drawing<br>2.0 x 2.0 x 0.5 mm Body<br>0.5mm Pitch DFN                                                                                                              |               |
| XXX±                           |         |                                                                                                                                                                                                      |               |
| XXXX±                          |         | <b>SIZE</b> C<br><b>DRAWING No.</b> PSC-4490                                                                                                                                                         | <b>REV</b> 01 |
| DO NOT SCALE DRAWING           |         |                                                                                                                                                                                                      | SHEET 1 OF 2  |

| REVISIONS                                    |     |                     |        |
|----------------------------------------------|-----|---------------------|--------|
| DATE CREATED                                 | REV | DESCRIPTION         | AUTHOR |
| 09/18/14                                     | 00  | INITIAL RELEASE     | J.HUA  |
| 4/5/18                                       | 01  | CHANGE VFQFN to DFN | R.C    |
| NOTE: REFER TO DCP FOR OFFICIAL RELEASE DATE |     |                     |        |






RECOMMENDED LAND PATTERN DIMENSION

NOTES:

1. ALL DIMENSION ARE IN MM. ANGLES IN DEGREES.
2. TOP DOWN VIEW. AS VIEWED.
3. LAND PATTERN RECOMMENDATION PER IPC-7351B GENERIC REQUIREMENT FOR MOUNT DESIGN AND LAND PATTERN.

|                                |         |                                                                                                                                                                                                  |               |
|--------------------------------|---------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|
| TOLERANCES<br>UNLESS SPECIFIED |         |  <b>6024 SILVER CREEK VALLEY ROAD</b><br>San Jose, CA 95138<br>PHONE: (408) 284-8200<br>FAX: (408) 492-8674 |               |
| DECIMAL                        | ANGULAR |                                                                                                                                                                                                  |               |
| XX±                            | ±       | <b>TITLE</b> CMG8 Package Outline Drawing<br>2.0 x 2.0 x 0.5 mm Body<br>0.5mm Pitch DFN                                                                                                          |               |
| XXX±                           |         |                                                                                                                                                                                                  |               |
| XXXX±                          |         | <b>SIZE</b> C                                                                                                                                                                                    | <b>REV</b> 01 |
|                                |         | DO NOT SCALE DRAWING                                                                                                                                                                             |               |
|                                |         | SHEET 2 OF 2                                                                                                                                                                                     |               |

| REVISIONS                                   |     |                                                |        |
|---------------------------------------------|-----|------------------------------------------------|--------|
| DATE CREATED                                | REV | DESCRIPTION                                    | AUTHOR |
| 4/3/14                                      | 00  | INITIAL RELEASE                                | JH     |
| 12/11/14                                    | 01  | ADD PIN1 CHAMFER                               | JH     |
| 4/5/18                                      | 02  | CHANGE QFN TO VFQFPN, RECALCULATE LAND PATTERN | RC     |
| NOE: REFER TO DCP FOR OFFICIAL RELEASE DATE |     |                                                |        |




NOTES:

1. ALL DIMENSIONING AND TOLERANCING CONFORM TO ANSI Y14.5M-1982
2. ALL DIMENSIONS ARE IN MILLIMETERS.

|                                |                                                                                       |                                                                                                                                                                                                                        |              |
|--------------------------------|---------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|
| TOLERANCES<br>UNLESS SPECIFIED |                                                                                       |  <b>IDT™</b><br>6024 Silver Creek Valley Road<br>San Jose CA 95138<br>PHONE: (408) 284-8200<br>FAX: (408) 284-8591<br>www.IDT.com |              |
| DECIMAL                        | ANGULAR                                                                               |                                                                                                                                                                                                                        |              |
| X±                             | ±1°                                                                                   |                                                                                                                                                                                                                        |              |
| XX±                            |                                                                                       |                                                                                                                                                                                                                        |              |
| XXX±                           |                                                                                       |                                                                                                                                                                                                                        |              |
| DRAWN                          | TITLE CMG16 Package Outline Drawing<br>2.5 x 2.5 x 0.5 mm Body<br>0.40mm Pitch VFQFPN |                                                                                                                                                                                                                        |              |
|                                | SIZE<br>C                                                                             | DRAWING No.<br>PSC-4478                                                                                                                                                                                                | REV<br>02    |
|                                | DO NOT SCALE DRAWING                                                                  |                                                                                                                                                                                                                        | SHEET 1 OF 2 |
|                                |                                                                                       |                                                                                                                                                                                                                        |              |

| REVISIONS                                   |     |                                                |        |
|---------------------------------------------|-----|------------------------------------------------|--------|
| DATE CREATED                                | REV | DESCRIPTION                                    | AUTHOR |
| 4/3/14                                      | 00  | INITIAL RELEASE                                | JH     |
| 12/11/14                                    | 01  | ADD PIN1 CHAMFER                               | JH     |
| 4/5/18                                      | 02  | CHANGE QFN TO VFQFPN, RECALCULATE LAND PATTERN | RC     |
| NOE: REFER TO DCP FOR OFFICIAL RELEASE DATE |     |                                                |        |




RECOMMENDED LAND PATTERN DIMENSION

NOTES:


1. ALL DIMENSIONS ARE IN MM. ANGLES IN DEGREES.
2. TOP DOWN VIEW AS VIEWED ON PCB.
3. LAND PATTERN RECOMMENDATION PER IPC-7351B GENERIC REQUIREMENT FOR SURFACE MOUNT DESIGN AND LAND PATTERN.

|                                |         |                                                                                                                                                                                                                                                      |  |
|--------------------------------|---------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| TOLERANCES<br>UNLESS SPECIFIED |         |  <b>IDT™</b> 6024 Silver Creek Valley Road<br>San Jose CA 95138<br>PHONE: (408) 284-8200<br>FAX: (408) 284-8591<br><a href="http://www.IDT.com">www.IDT.com</a> |  |
| DECIMAL                        | ANGULAR |                                                                                                                                                                                                                                                      |  |
| X±                             | ±1°     | <b>TITLE</b> CMG16 Package Outline Drawing<br>2.5 x 2.5 x 0.5 mm Body<br>0.40mm Pitch VFQFPN                                                                                                                                                         |  |
| XX±                            |         |                                                                                                                                                                                                                                                      |  |
| XXX±                           |         | <b>SIZE</b> C <b>DRAWING No.</b> PSC-4478 <b>REV</b> 02                                                                                                                                                                                              |  |
| DRAWN                          |         | DO NOT SCALE DRAWING                                                                                                                                                                                                                                 |  |
|                                |         | SHEET 2 OF 2                                                                                                                                                                                                                                         |  |



**NOTE:**

1. ALL DIMENSIONS ARE IN MM.
2. ALL DIMENSIONING AND TOLERANCING CONFORM TO ASME Y14.5-2009
3. PIN 1 LOCATION IDENTIFIER IS EITHER BY CHAMFER OR NOTCH




## RECOMMENDED LAND PATTERN DIMENSION


### NOTES:

1. ALL DIMENSIONS ARE IN MM. ANGLES IN DEGREES.
2. TOP DOWN VIEW. AS VIEWED ON PCB.
3. LAND PATTERN RECOMMENDATION PER IPC-7351B GENERIC REQUIREMENT FOR SURFACE MOUNT DESIGN AND LAND PATTERN.


| Package Revision History |         |                      |
|--------------------------|---------|----------------------|
| Date Created             | Rev No. | Description          |
| Sept 13, 2018            | Rev 01  | Change QFN to VFQFPN |
| Mar 30, 2016             | Rev 00  | Initial Release      |




TOP VIEW



SIDE VIEW




BOTTOM VIEW



NOTES:

1. ALL DIMENSIONING AND TOLERANCING CONFORM TO ANSI Y14.5M-1982
2. ALL DIMENSIONS ARE IN MILLIMETERS



RECOMMENDED LAND PATTERN DIMENSION

- NOTES:
- 1. ALL DIMENSION ARE IN MM. ANGLES IN DEGREES.
  - 2. TOP DOWN VIEW. AS VIEWED.
  - 3. LAND PATTERN RECOMMENDATION PER IPC-7351B GENERIC REQUIREMENT FOR MOUNT DESIGN AND LAND PATTERN.

| Package Revision History |         |                 |
|--------------------------|---------|-----------------|
| Date Created             | Rev No. | Description     |
|                          |         |                 |
| Oct 23, 2018             | Rev 00  | Initial Release |

## IMPORTANT NOTICE AND DISCLAIMER

RENESAS ELECTRONICS CORPORATION AND ITS SUBSIDIARIES ("RENESAS") PROVIDES TECHNICAL SPECIFICATIONS AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, WITHOUT LIMITATION, ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for developers skilled in the art designing with Renesas products. You are solely responsible for (1) selecting the appropriate products for your application, (2) designing, validating, and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, or other requirements. These resources are subject to change without notice. Renesas grants you permission to use these resources only for development of an application that uses Renesas products. Other reproduction or use of these resources is strictly prohibited. No license is granted to any other Renesas intellectual property or to any third party intellectual property. Renesas disclaims responsibility for, and you will fully indemnify Renesas and its representatives against, any claims, damages, costs, losses, or liabilities arising out of your use of these resources. Renesas' products are provided only subject to Renesas' Terms and Conditions of Sale or other applicable terms agreed to in writing. No use of any Renesas resources expands or otherwise alters any applicable warranties or warranty disclaimers for these products.

(Rev.1.0 Mar 2020)

### Corporate Headquarters

TOYOSU FORESIA, 3-2-24 Toyosu,  
Koto-ku, Tokyo 135-0061, Japan  
[www.renesas.com](http://www.renesas.com)

### Contact Information

For further information on a product, technology, the most up-to-date version of a document, or your nearest sales office, please visit:  
[www.renesas.com/contact/](http://www.renesas.com/contact/)

### Trademarks

Renesas and the Renesas logo are trademarks of Renesas Electronics Corporation. All trademarks and registered trademarks are the property of their respective owners.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## Renesas Electronics:

[5PB1108PGGI](#) [5PB1108CMGI](#) [5PB1110NDGI](#) [5PB1110PGGI](#) [5PB1104PGGI](#) [5PB1104CMGI](#) [5PB1102PGGI](#)  
[5PB1102CMGI](#) [5PB1106CMGI](#) [5PB1106PGGI](#) [5PB1108PGGI8](#) [5PB1106CMGI8](#) [5PB1108CMGI8](#) [5PB1110NDGI8](#)  
[5PB1102CMGI8](#) [5PB1106PGGI8](#) [5PB1102PGGI8](#) [5PB1104CMGI8](#) [5PB1110PGGI8](#) [5PB1104PGGI8](#)  
[5PB1104CMGI/W](#) [5PB1102PGGK](#) [5PB1104PGGK8](#) [5PB1104PGGK](#) [5PB1104CMGK](#) [5PB1102CMGK8](#)  
[5PB1102PGGK8](#) [5PB1102CMGK](#) [5PB1104CMGK8](#) [5PB1106CMGK8](#) [5PB1108CMGK8](#) [5PB1106PGGK8](#)  
[5PB1106PGGK](#) [5PB1110NDGK8](#) [5PB1110NDGK](#) [5PB1108CMGK](#) [5PB1108PGGK](#) [5PB1106CMGK](#) [5PB1110PGGK](#)  
[5PB1110PGGK8](#) [5PB1108PGGK8](#)