

NBA3N012C

3.3 V Automotive Grade LVDS Line Receiver

Description

The NBA3N012C is a single LVCMOS Output Differential Line Receiver for Low Power and high data rate Automotive applications. The device is optimized to support data rate higher than 400 Mbps (200 MHz). The NBA3N012C accept directly LVDS signal as an input and translate it to LVCMOS output levels. The device includes an input termination resistor minimizing number of the external components for point to point interface.

The NBA3N012C is offered in 5 lead SOT23 package and it is shipping in 3000 pcs tape & reel.

Features

- Compatible with TIA/EIA-644A Standard
- Automotive Grade AECQ-100 Grade 1
- > 400 Mbps (200 MHz) Data Rate
- Operating Range: $V_{DD} = 3.3 \text{ V} \pm 0.3 \text{ V}$
- Typical 100 ps Differential Skew
- Maximum Propagation Delay of 3.5 ns
- Low Power Dissipation (Typical 20 mW @ 3.3 V)
- SOT23-5 Lead Package with Pinout optimized for easy PCB Layout
- Integrated Line Termination Resistor of 100 Ω
- Power Down High Impedance on LVDS Pins
- Inputs Accept LVDS/CML/LVPECL Signals
- Temperature Operating Range -40°C to $+125^{\circ}\text{C}$
- These are Pb-Free Devices

Typical Applications:

- Automotive: Head Lamp Lighting for Cars
- Telecom: Wireless, Microwave and Optical

Table 1. PIN DESCRIPTION

| Pin Number | Pin Name | I/O Type | Description |
|------------|------------------------|----------|-------------------------|
| 1 | V_{DD} | | Power Supply Pin |
| 2 | GND | | Ground Pin |
| 3 | IN | Input | Non-Inverting Input Pin |
| 4 | $\overline{\text{IN}}$ | Input | Inverting Input Pin |
| 5 | Q | Output | Output Pin |

Table 2. TRUTH TABLE

| Inputs | Output |
|---|--------|
| [IN] – [$\overline{\text{IN}}$] | Q |
| $V_{ID} \geq +0.1 \text{ V}$ | H |
| $V_{ID} \leq -0.1 \text{ V}$ | L |
| Full Fail Safe OPEN/SHORT or terminated | H or L |




ON Semiconductor®

www.onsemi.com



**SOT23-5
DT SUFFIX
CASE 527AH**


MARKING DIAGRAM




12C = Specific Device Code
 A = Assembly Code
 Y = Year
 W = Work Week
 ■ = Pb-Free Package

(Note: Microdot may be in either location)

LOGIC DIAGRAM



PINOUT DIAGRAM



ORDERING INFORMATION

| Device | Package | Shipping† |
|----------------|-------------------|--------------------|
| NBA3N012CSNT1G | SOT23-5 (Pb-Free) | 3000 / Tape & Reel |

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specification Brochure, BRD8011/D.

NBA3N012C

Table 3. ATTRIBUTES (Note 1)

| Characteristics | | | Value |
|-------------------------------|---|----------|---------------------------------------|
| ESD Protection | Human Body Model (JEDEC Standard 22, Method A114-E) | All Pins | ≥ 8 kV |
| | Charge Device Model (JEDEC Standard 22, Method C101D) | All Pins | ≥ 1.25 kV |
| Moisture Sensitivity (Note 1) | | | Level 1 |
| Flammability Rating | Oxygen Index: 28 to 34 | | UL 94 Code V-0 A 0.125 in 28 to 34 |

1. For additional information, see Application Note AND8003/D

Table 4. MAXIMUM RATINGS (Note 2)

| Symbol | Parameter | Rating | Unit |
|------------------|--|-----------------------------------|------|
| V _{DD} | Supply voltage | -0.30 ≤ V _{DD} ≤ +4.0 | V |
| V _{IN} | Input Voltage (IN, \overline{IN}) LVDS | -0.30 to +3.90 | V |
| V _Q | Output Voltage (Pin Q) LVCMOS | -0.30 to (V _{DD} + 0.30) | V |
| I _{OS} | Output Short Circuit Current (Pin Q) | -100 | mA |
| T _j | Maximum Junction Temperature | 135 | °C |
| T _{stg} | Storage Temperature Range | -65 to +150 | °C |
| θ _{JC} | Thermal resistance (Junction-to-Case) – (Note 3) | 107 | °C/W |
| θ _{JA} | Thermal resistance (Junction-to-Ambient) – (Note 3) | 138.5 | °C/W |
| T _{sol} | Lead Temperature Soldering (4 Seconds) – SOLDERM/D | 260 | °C |
| PD | Package Power Dissipation @ 25°C – Derating of 7.22 mW/°C above 25°C | 794 | mW |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

2. The maximum ratings applied are individual stress limit values and not valid simultaneously.

3. JEDEC standard multilayer board –2S2P (2 signal 2 power)

Table 5. DC CHARACTERISTICS V_{DD} = 3.3 V ± 0.3 V, GND = 0 V, T_A –40°C to +125°C (Note 4)

| Symbol | Parameter | Test Conditions | Min | Typ | Max | Unit |
|-----------------|------------------------------|--|------|------|------|------|
| I _{DD} | No Load Supply Current | Pin: V _{DD} ; Inputs Open | | 5.4 | 9 | mA |
| V _{OH} | Output High Voltage | Pin: Q; I _{OH} = -0.4 mA, Inputs shorted or terminated, V _{ID} = +200 mV | 2.4 | 3.1 | | V |
| V _{OL} | Output Low Voltage | Pin: Q; I _{OL} = 2 mA, V _{ID} = -200 mV | | 0.3 | 0.5 | V |
| I _{OS} | Output Short Circuit Current | Pin: Q; V _Q = 0 V | -15 | -50 | -100 | mA |
| V _{CL} | Input Clamp Voltage | I _{CL} = -18 mA | -1.5 | -0.7 | | V |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

4. – minus sign indicated only direction. Current into the device is defined as positive. I_{OS} is specified as magnitude only.

Table 6. ELECTRICAL CHARACTERISTICS V_{DD} = 3.3 V ± 0.3 V, GND = 0 V, T_A –40°C to +125°C, Pin: IN/ \overline{IN} (Note 5)

| Symbol | Parameter | Test Conditions | Min | Typ | Max | Unit |
|------------------|-----------------------------------|--|------|-----|------|------|
| V _{TH} | Differential Input High Threshold | V _{CM} dependent on V _{DD} | | +30 | +100 | mV |
| V _{TL} | Differential Input Low Threshold | | -100 | -30 | | mV |
| V _{CM} | Offset Voltage | | 0.1 | | 2.35 | V |
| I _{IN} | Input Current | V _{IN} = +2.8 V V _{DD} = 0 V or 3.6 V | -10 | ±1 | +10 | μA |
| | | V _{IN} = 0 V | -10 | ±1 | +10 | μA |
| | | V _{IN} = +3.6 V V _{DD} = 0 V | -20 | | +20 | μA |
| I _{IND} | Differential Input Current | V _{IN} = +0.4 V, V \overline{IN} = +0 V | 3.0 | 3.9 | 4.4 | mA |
| | | V _{IN} = +2.4 V, V \overline{IN} = +2.0 V | | | | |
| R _T | Integrated Termination Resistor | | | 100 | | Ω |
| C _{IN} | Input Capacitance | IN = \overline{IN} = GND | | 3 | | pF |

5. – minus sign indicated only direction. Current into the device is defined as positive.

Table 7. SWITCHING CHARACTERISTICS

$V_{DD} = 3.3 \text{ V} \pm 0.3 \text{ V}$, $GND = 0 \text{ V}$, $T_A = -40^\circ\text{C}$ to $+125^\circ\text{C}$, $F = 1 \text{ MHz}$, $Z_O = 50 \Omega$, $t_r, t_f \leq 3 \text{ ns}$ (0% to 100%) – (Note 6)

| Symbol | Parameters | Min | Typ | Max | Unit |
|----------------|--|-----|-----|-----|------|
| $t_{pHL D}$ | High to Low Differential Propagation Delay | 1.0 | 1.8 | 3.5 | ns |
| $t_{pLH D}$ | Low to High Differential Propagation Delay | 1.0 | 1.7 | 3.5 | ns |
| t_r | Rise Time – Transition Low to High | | 350 | 800 | ps |
| t_f | Fall Time – Transition High to Low | | 175 | 800 | ps |
| $t_{SKD(P)}$ | Differential Pulse Skew $ t_{pHL D} - t_{pLH D} $ (Note 7) | 0 | 100 | 400 | ps |
| $t_{SKD(PP)1}$ | Part to Part Skew – (Note 8) | 0 | 0.3 | 1.0 | ns |
| $t_{SKD(PP)2}$ | Part to Part Skew – (Note 9) | 0 | 0.4 | 2.5 | ns |
| f_{MAX} | Maximum Operating Frequency – (Note 10) | | 250 | | MHz |

6. Test Conditions for the above – $V_{ID} = 200 \text{ mV}$, $C_L = 15 \text{ pF}$ (includes Load & Jig Capacitance), Figures 1 and 2
7. $|t_{pHL D} - t_{pLH D}|$, is the magnitude difference in differential propagation delay time between the positive going edge and the negative going edge of the same channel.
8. Differential Part to Part Skew, is defined as the difference between the minimum and maximum specified differential propagation delays. This specification applies to devices at the same V_{DD} and within 5°C of each other within the operating temperature range.
9. Part to part skew, is the differential channel to channel skew of any event between devices. This specification applies to devices over recommended operating temperature and voltage ranges, and across process distribution. t_{SKD2} is defined as $|Max - Min|$ differential propagation delay.
10. f_{MAX} Input Conditions: $t_r = t_f < 1 \text{ ns}$ (0% to 100%), Duty Cycle 50%, differential (1.05 V to 1.35 V Peak to Peak). f_{MAX} Output Conditions: V_{OL} (Max 0.4 V), V_{OH} (min 2.4 V), Load = 15 pF (stray + probe), Duty Cycle 60%/40%

PARAMETER MEASUREMENT:




Figure 1. Receiver Propagation Delay & Transition Time Test Circuit





Figure 2. Receiver Propagation Delay & Transition Time Waveforms

NBA3N012C


PACKAGE DIMENSIONS

SOT-23, 5 Lead
CASE 527AH
ISSUE O




TOP VIEW

| SYMBOL | MIN | NOM | MAX |
|------------|----------|------|------|
| A | 0.90 | | 1.45 |
| A1 | 0.00 | | 0.15 |
| A2 | 0.90 | 1.15 | 1.30 |
| b | 0.30 | | 0.50 |
| c | 0.08 | | 0.22 |
| D | 2.90 BSC | | |
| E | 2.80 BSC | | |
| E1 | 1.60 BSC | | |
| e | 0.95 BSC | | |
| L | 0.30 | 0.45 | 0.60 |
| L1 | 0.60 REF | | |
| L2 | 0.25 REF | | |
| θ | 0° | 4° | 8° |
| $\theta 1$ | 5° | 10° | 15° |
| $\theta 2$ | 5° | 10° | 15° |



SIDE VIEW



END VIEW

Notes:

- (1) All dimensions in millimeters. Angles in degrees.
- (2) Complies with JEDEC standard MO-178.

ON Semiconductor and are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800-282-9855 Toll Free
USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81-3-5817-1050

ON Semiconductor Website: www.onsemi.com
Order Literature: <http://www.onsemi.com/orderlit>
For additional information, please contact your local Sales Representative

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[ON Semiconductor:](#)

[NBA3N012CSNT1G](#)